



NOTES:

1. CONTRACTOR SHALL REPLACE PAVEMENT TO THE SAME CROSS SECTION AS EXISTED PRIOR TO REMOVAL.
2. CONTRACTOR SHALL BE REQUIRED TO PROVIDE TRAFFIC CONTROL AND DEVICES AS REQUIRED BY THE M.U.T.C.D. OR NC SUPPLEMENT. WORK CANNOT PROCEED UNTIL THE MEASURES ARE IN PLACE. CONTRACTOR SHALL BE RESPONSIBLE TO PROTECT NEW PAVEMENT FROM TRAFFIC AND OTHER SOURCES OF DAMAGE.
3. UNDER NO CIRCUMSTANCES SHALL THE DISTURBED AREA EXTEND BEYOND THE RIGHT-OF-WAY AND/OR THE EASEMENT LIMITS. UNLESS OTHERWISE APPROVED BY THE FAYPWC PROJECT COORDINATOR.
4. THE FINAL PRODUCT SHALL BE SUBJECT TO THE OWNER'S APPROVAL.
5. SAWCUT CONCRETE DRIVE STRAIGHT AND TRUE. JAGGED SAWCUTS SHALL NOT BE ACCEPTABLE. SAWCUTS SHALL BE STRAIGHT UNIFORM WIDTHS PERPENDICULAR TO THE DRIVEWAY.
6. MINIMUM RESIDENTIAL CONCRETE DRIVEWAY THICKNESS SHALL BE 5". MINIMUM COMMERCIAL CONCRETE DRIVEWAY THICKNESS SHALL BE 7".
7. CONTRACTOR SHALL CONTACT THE CITY OF FAYETTEVILLE'S CONSTRUCTION MANAGEMENT DEPARTMENT AT (910) 433-1656 A MINIMUM OF 24 HOURS IN ADVANCE FOR AN INSPECTION OF THE CONCRETE FORMS.
8. PROVIDE EXPANSION JOINT(S) AS REQUIRED BY THE CITY OF FAYETTEVILLE FOR FUTURE SIDEWALK PLACEMENT.
9. CURING COMPOUND SHALL BE UTILIZED, AS SPECIFIED BY THE CITY OF FAYETTEVILLE.
10. NEW EXPANSION JOINTS SHALL BE PLACED 4 TO 10 FEET FROM EXISTING EXPANSION JOINTS, AS SPECIFIED BY THE FAYPWC PROJECT COORDINATOR.
11. ALL CONSTRUCTION SHALL BE IN ACCORDANCE WITH CITY OF FAYETTEVILLE REQUIREMENTS.

CONCRETE DRIVEWAY PATCH N.T.S.			FAYETTEVILLE PUBLIC WORKS COMMISSION FAYETTEVILLE, N.C.			NO.	DATE	REVISION
SHEET NO. 1 OF 1	DWG. NO. M.5	DWG. BY: FAYPWC	WATER RESOURCES ENGINEERING DEPARTMENT					
	DATE: JAN. 01, 2025	APPROVED BY: K.A.H.						